
Stream:	Internet Engineering Task Force (IETF)	
RFC:	9844	
Obsoletes:	6874	
Updates:	4007 , 7622 , 8089	
Category:	Standards Track	
Published:	August 2025	
ISSN:	2070-1721	
Authors:	B. Carpenter <i>Univ. of Auckland</i>	R. Hinden <i>Check Point Software</i>

RFC 9844

Entering IPv6 Zone Identifiers in User Interfaces

Abstract

This document describes how the zone identifier of an IPv6 scoped address, defined in the IPv6 Scoped Address Architecture specification (RFC 4007), should be entered into a user interface. This document obsoletes RFC 6874 and updates RFCs 4007, 7622, and 8089.

Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in Section 2 of RFC 7841.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <https://www.rfc-editor.org/info/rfc9844>.

Copyright Notice

Copyright (c) 2025 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

Table of Contents

1. Introduction	2
2. Use Cases	3
3. Relationship to Other Documents	3
4. Requirements Language	4
5. Specification	4
6. Security Considerations	5
7. IANA Considerations	6
8. References	6
8.1. Normative References	6
8.2. Informative References	6
Acknowledgements	7
Authors' Addresses	8

1. Introduction

A number of software tools require or permit the user to enter an IPv6 address via a user interface (UI). The standard literal text format for an IPv6 address is defined by [\[RFC4291\]](#) and [\[RFC5952\]](#). The IPv6 Scoped Address Architecture specification [\[RFC4007\]](#) extends the text representation of limited-scope IPv6 addresses, in particular link-local unicast addresses and multicast addresses with less than global scope, such that a zone identifier may be concatenated to an address. Note that [\[RFC5952\]](#) does not mention this extension.

Zone identifiers are especially useful in contexts in which literal addresses are typically used, for example, during fault diagnosis or device configuration (where a device may be physical or virtual) when it may be essential to specify which interface is used for sending to a link-local address. It should be noted that zone identifiers have purely local meaning within the node in which they are defined, usually being the same as IPv6 interface names. They are completely meaningless for any other node. At the time of writing, they are meaningful only when attached to link-local unicast and scoped multicast addresses, but it is possible that other uses might be defined in the future.

Examples of a link-local unicast address qualified by a zone identifier are "fe80::1234%eth0" on a Linux host or "fe80::4321%7" on a Microsoft Windows host.

Such addresses are directly supported by socket API calls including "getaddrinfo()" [\[RFC3493\]](#).

Devices whose network stack does not support the model of a human-readable zone identifier described in [RFC4007] are out of scope for this document.

2. Use Cases

Some examples of use cases for entering an address that includes a zone identifier into a UI are as follows:

1. A software tool may be used for simple debugging actions involving link-local addresses on a host with more than one active link interface. For example, the functioning of an interface and the existence of a device may be checked via "ping fe80::1234%eth0". If this succeeds, the user learns that the other device is reachable via the interface named "eth0".
2. A software tool must sometimes be used to configure or reconfigure a device that only has a link-local address, again in a host with more than one active link interface. For example, a typical home router may be configured via a well-known private address [RFC1918] such as "192.168.178.1" but not via "fe80::1%eth0", if the tool in use does not support the input of zone identifiers. More generally, link-local addresses need to be entered in network management UIs for use in formats such as YANG [RFC6991].
3. Using a monitoring tool such as a network sniffer, the user may need to specify a given link-local address on a given interface whose traffic is of interest. (For example, at the time of writing, Wireshark supports capture from multiple interfaces but does not appear to support the zone identifier in a display filter.)
4. The Microsoft Web Services for Devices (WSD) virtual printer port mechanism can present the user with an IPv6 link-local address such as "fe80::823b:f9ff:fe7b:d9dc%10" in which the zone identifier is present but is not recognized by appropriate software.
5. The National Marine Electronics Association (NMEA) has defined the "OneNet Marine IPv6 Ethernet Networking Standard" [ONE-NET], which uses IPv6 link-local addresses exclusively. Proposed improvements to the standard include a web page for device configuration using link-local addresses.

Such requirements have already spawned hacks to work around current limitations (e.g., the hack described in [LL-HACK], which is no longer maintained and has been archived).

For all such use cases, it is highly desirable that a complete IPv6 link-local address can be cut and pasted from one UI (such as the output from a system command) to another. Since such addresses may include quite long hexadecimal strings, for example, "fe80::8d0f:7f26:f5c8:780b%enx525400d5e0fb", any solution except cut-and-paste is highly error prone.

3. Relationship to Other Documents

The use cases listed above apply to relatively simple actions on end systems. The zone identifiers that can be used are limited by the host operating system, since [RFC4007] only specifies that they are text strings, without specifying a maximum length or syntax. As [RFC4007] explains, each zone identifier corresponds to a numerical zone index that qualifies a link-local address.

It should be noted that whereas some operating systems and network APIs support a default zone identifier as recommended by [\[RFC4007\]](#), others, including Linux, do not, and for them a solution is particularly important, since a link-local address without a zone index cannot be used in the Linux socket API.

The model in [\[RFC4007\]](#) assumes that the human-readable zone identifier is mapped by the operating system into a numeric interface index. Typically, this mapping is performed by the socket API, e.g., by "getaddrinfo()". The mapping between the human-readable zone identifier string and the numeric value is a host-specific function that varies between operating systems. The present document is concerned only with the human-readable string that is typically displayed in an operating system's user interface. However, in most operating systems, it is possible to use the underlying interface number, represented as a decimal integer, as an equivalent to the human-readable string. This is recommended by [Section 11.2](#) of [\[RFC4007\]](#), but it is not required. This possibility does not affect the UI requirement given in this document.

As IPv6 deployment becomes more widespread, the lack of a solution for handling complete link-local addresses in all tools is becoming an acute problem for increasing numbers of operational and support personnel. It will become critical as IPv6-only or IPv6-mostly networks [\[RFC8925\]](#) [\[IPv6-MOSTLY\]](#), with nodes lacking native IPv4 support, appear. For example, the NMEA use case mentioned above is an immediate requirement. This is the principal reason for documenting this requirement now.

This document completely obsoletes [\[RFC6874\]](#), which implementors of web browsers have determined is impracticable to support [\[LINK-LOCAL-URI\]](#), and replaces it with a generic UI requirement. Note that obsoleting [\[RFC6874\]](#) reverts the change that it made to the URI syntax defined by [\[RFC3986\]](#), so [\[RFC3986\]](#) is no longer updated by [\[RFC6874\]](#). As far as is known, this change will have no significant impact on non-browser deployments of URIs.

This document also updates [\[RFC7622\]](#) and [\[RFC8089\]](#) by deleting their references to [\[RFC6874\]](#).

It also updates [\[RFC4007\]](#) by adding a new requirement that user interfaces support the zone identifier as described in [Section 5](#).

4. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [\[RFC2119\]](#) [\[RFC8174\]](#) when, and only when, they appear in all capitals, as shown here.

5. Specification

A user interface (UI) that allows or requires the user to enter an IPv6 address other than a global unicast address **MUST** provide a means for entering a link-local address or a scoped multicast address and selecting a zone identifier as specified by [\[RFC4007\]](#) (typically, an interface identifier as defined by the operating system).

In this case, the UI **SHOULD** support the complete format specified by [RFC4007] (e.g., "fe80::1%eth0").

If this is impossible for practical reasons, the UI **MAY** support an alternative delimiter in place of "%". The hyphen ("-") is suggested (e.g., "fe80::1-eth0").

If this too is impossible for practical reasons, the UI **MAY** provide two separate input fields (e.g., "fe80::1" in one box and "eth0" in another), selection from a list of active zone identifiers, or a separate command-line parameter for the zone identifier.

The program providing the UI will then store the address and the zone identifier, converting the latter to an interface index (typically via the socket API). A faulty zone identifier will be detected when attempting to convert it, and this should be reported to the user as an error. The resulting interface index will be used for any subsequent socket calls using the link-local address.

Note that an address string such as "fe80::1%eth0" cannot be converted to binary by the POSIX socket API function "inet_pton()" [POSIX]. It must be converted either by using "getaddrinfo()" or by splitting it into two strings and using "inet_pton()" and "if_nametoindex()" successively, in order to obtain the required interface index value.

In this model, the zone identifier is considered independently of the IPv6 address itself. However, this does not in itself resolve the difficulties in considering the zone identifier as part of the HTTP origin model [RFC6454]. Therefore, this approach does not resolve the issue of how browsers should support link-local addresses, which is discussed further in [LINK-LOCAL-URI]. Because of this, the recommendations and normative statements in this document do not apply to URIs fetched by web browsers.

6. Security Considerations

As explained in [RFC4007], zone identifiers are of local significance only and must not be sent on the wire. In particular, see the final security consideration of [RFC4007], which indicates that software should not trust packets that contain textual non-global addresses as data. Therefore, software that obtains a zone identifier through a UI should not transmit it further.

There is no formal limit on the length of the zone identifier string in [RFC4007]. A UI implementation should apply an appropriate length limit when inputting a zone identifier, in order to minimize the risk of a buffer overrun. Typically, this limit would be the same as the host operating system's limit on interface names.

[RFC4007] does not specify or restrict the character set allowed in a zone identifier. Therefore, each implementation processing zone identifiers needs to make checks appropriate for the environment it is used in. For example, a UI implementation should not allow ASCII NUL characters in a zone identifier string as this could cause inconsistencies in subsequent string processing.

7. IANA Considerations

This document has no IANA actions.

8. References

8.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC4007] Deering, S., Haberman, B., Jinmei, T., Nordmark, E., and B. Zill, "IPv6 Scoped Address Architecture", RFC 4007, DOI 10.17487/RFC4007, March 2005, <<https://www.rfc-editor.org/info/rfc4007>>.
- [RFC4291] Hinden, R. and S. Deering, "IP Version 6 Addressing Architecture", RFC 4291, DOI 10.17487/RFC4291, February 2006, <<https://www.rfc-editor.org/info/rfc4291>>.
- [RFC5952] Kawamura, S. and M. Kawashima, "A Recommendation for IPv6 Address Text Representation", RFC 5952, DOI 10.17487/RFC5952, August 2010, <<https://www.rfc-editor.org/info/rfc5952>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

8.2. Informative References

- [IPv6-MOSTLY] Buraglio, N., Caletka, O., and J. Linkova, "IPv6-Mostly Networks: Deployment and Operations Considerations", Work in Progress, Internet-Draft, draft-ietf-v6ops-6mops-01, 3 March 2025, <<https://datatracker.ietf.org/doc/html/draft-ietf-v6ops-6mops-01>>.
- [LINK-LOCAL-URI] Schinazi, D., "Best Practices for Link-Local Connectivity in URI-Based Protocols", Work in Progress, Internet-Draft, draft-schinazi-httpbis-link-local-uri-bcp-03, 22 February 2024, <<https://datatracker.ietf.org/doc/html/draft-schinazi-httpbis-link-local-uri-bcp-03>>.
- [LL-HACK] Jin, P., "Snippets: IPv6 link-local connect hack", 2021, <https://web.archive.org/web/20210725030713/https://website.peterjin.org/wiki/Snippets:IPv6_link_local_connect_hack>.
- [ONE-NET] NMEA, "OneNet Marine IPv6 Ethernet Networking Standard", 2025, <<https://www.nmea.org/nmea-onenet.html>>.

- [POSIX]** IEEE, "IEEE/Open Group Standard for Information Technology--Portable Operating System Interface (POSIX™) Base Specifications, Issue 8", IEEE Std 1003.1-2024, DOI 10.1109/IEEESTD.2024.10555529, June 2024, <<https://doi.org/10.1109/IEEESTD.2024.10555529>>.
- [RFC1918]** Rekhter, Y., Moskowitz, B., Karrenberg, D., de Groot, G. J., and E. Lear, "Address Allocation for Private Internets", BCP 5, RFC 1918, DOI 10.17487/RFC1918, February 1996, <<https://www.rfc-editor.org/info/rfc1918>>.
- [RFC3493]** Gilligan, R., Thomson, S., Bound, J., McCann, J., and W. Stevens, "Basic Socket Interface Extensions for IPv6", RFC 3493, DOI 10.17487/RFC3493, February 2003, <<https://www.rfc-editor.org/info/rfc3493>>.
- [RFC3986]** Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, RFC 3986, DOI 10.17487/RFC3986, January 2005, <<https://www.rfc-editor.org/info/rfc3986>>.
- [RFC6454]** Barth, A., "The Web Origin Concept", RFC 6454, DOI 10.17487/RFC6454, December 2011, <<https://www.rfc-editor.org/info/rfc6454>>.
- [RFC6874]** Carpenter, B., Cheshire, S., and R. Hinden, "Representing IPv6 Zone Identifiers in Address Literals and Uniform Resource Identifiers", RFC 6874, DOI 10.17487/RFC6874, February 2013, <<https://www.rfc-editor.org/info/rfc6874>>.
- [RFC6874bis]** Carpenter, B., Cheshire, S., and R. Hinden, "Representing IPv6 Zone Identifiers in Address Literals and Uniform Resource Identifiers", Work in Progress, Internet-Draft, draft-ietf-6man-rfc6874bis-09, 2 July 2023, <<https://datatracker.ietf.org/doc/html/draft-ietf-6man-rfc6874bis-09>>.
- [RFC6991]** Schoenwaelder, J., Ed., "Common YANG Data Types", RFC 6991, DOI 10.17487/RFC6991, July 2013, <<https://www.rfc-editor.org/info/rfc6991>>.
- [RFC7622]** Saint-Andre, P., "Extensible Messaging and Presence Protocol (XMPP): Address Format", RFC 7622, DOI 10.17487/RFC7622, September 2015, <<https://www.rfc-editor.org/info/rfc7622>>.
- [RFC8089]** Kerwin, M., "The "file" URI Scheme", RFC 8089, DOI 10.17487/RFC8089, February 2017, <<https://www.rfc-editor.org/info/rfc8089>>.
- [RFC8925]** Colitti, L., Linkova, J., Richardson, M., and T. Mrugalski, "IPv6-Only Preferred Option for DHCPv4", RFC 8925, DOI 10.17487/RFC8925, October 2020, <<https://www.rfc-editor.org/info/rfc8925>>.

Acknowledgements

This document owes a lot to the previous discussions that led to [RFC6874] and to the expired Internet-Draft [RFC6874bis].

Useful comments were received from Erik Auerswald, Nick Buraglio, Martin J. Dürst, Toerless Eckert, David Farmer, Brian Haberman, Nate Karstens, Tero Kivinen, Erik Kline, Jen Linkova, Eduard Metz, Gyan Mishra, David Schinazi, Jürgen Schönwälder, Michael Sweet, Martin Thomson, Ole Troan, Éric Vyncke, Magnus Westerlund, and other participants in the 6MAN WG.

Authors' Addresses

Brian Carpenter

School of Computer Science

University of Auckland

PB 92019

Auckland 1142

New Zealand

Email: brian.e.carpenter@gmail.com

Robert M. Hinden

Check Point Software

959 Skyway Road

San Carlos, CA 94070

United States of America

Email: bob.hinden@gmail.com